

Kraft

Slitter winder



	TP - KRB 15	TP - KRS 20	TP - KRH 22	TP - KRP 24
Basis weight	80 ÷ 240 gsm	80 ÷ 240 gsm	80 ÷ 240 gsm	80 ÷ 240 gsm
Speed up to	1.600 m/min	2.000 m/min	2.200 m/min	2.400 m/min
Finished reel diam. up to	1.300 mm	1.600 mm	1.800 mm	1.800 mm
Trim width up to	2.800 mm	3.200 mm	4.200 mm	5.200 mm
Carrying drum	600 mm	650 mm	750 mm	850 mm
Relieving system	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Standard equipment

- Axial adjustment of parent reel
- Automatic empty spool removal
- Empty spool parking
- Automatic tension control
- Set web length or reel diameter control
- Automatic finished reel change
- Unloading table for finished reels
- Tangential slitting system
- Manual slitters positioning
- Rider roll pressure control
- Hydraulic and pneumatic on board plants
- Safety protections
- Trim removal system
- Operator friendly control system
- Easy access for maintenance

Options

- Automatic slitters positioning
- Visualization of slitters positioning
- Dust removal system
- Drive on chucks
- Drive on rider roll
- Automatic core feeding
- Automatic gluing on cores
- Automatic gluing on tail for reel sealing

Designed to process all grades of uncoated paper, Kraft, Packaging paper and corrugated products or board. Produces high quality paper reels with perfect consistency and diameter according to custom specifics